

- Material:**
- 1.Panel: 1.2mm/SPCC with Black color painting.
 - 2.RJ45 Housing: PC
 - 3.RJ45 Contact material & finished
 - 3-1. Phosphor Bronze with 50-60 micro-Inch Nickel plated.
 - 3-2. Contact area: 3-50 micro-Inch Gold plated
 - 4.IDC Housing: PC
 - 5.IDC Terminal material & finished
 - 5-1. Phosphor Bronze with 50 micro-Inch Tin-Lead plated.
 - 5-2. Over 50-60 micro-Inch Nickel plated.
 - 5-3. Use for 22-26 AWG stranded and solid wire
 6. Jack Bracket Set: ABS Black color
 - 7.PCB: FR4 UL 94V0


- Performance:**
- a. The IDC color combine two wirings of T568A & T568B.
 - b. Insertion Force: 900 gms for 8 contacts
 - c. Retention Strength: 7.7kgs between Jack and Plug
 - d. Operation Temperature: -40°C to 70°C.
 - e. Durability:
 - e-1. Jack: 750 cycles Plug-Jack mating and unmating test.
 - e-2. IDC: Max 200 punching times.

TITLE:		
	INCH	MM
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05
DRAWN BY	MA	
CHECK BY		
APPD BY		

 Shenzhen CopperLeaf Technology Co.,Ltd

TITLE: FTP Cat. 6 Patch Panel
24Port Krone IDC

P/N: CL-24PS-C601

SCALE	1:1		REV
UNIT	MM		
SHEET	1/1	DWG NO:	
DATE	2018/05/11		